

VELOCE / JET FC / LORE


Note: Lenses must be removed one at a time.

To Remove a Lens:

1. With the sunglasses facing you and the arms fully extended, pinch the nose bridge with your thumb and index finger. Pinch the outside edge of the lens with your opposite thumb and index finger.
2. Gently pull your hands apart as you pivot the lens down and out of its socket at the nose piece.
3. Pull the lens down and out of its anchor at the outside of the frame.
4. Repeat steps 1 -3 with the opposite lens. Lens will be more difficult to remove due to Z87.1 rating.

☹ Cleaning and Maintenance: Use the microfiber cleaning bag for storage. If glasses are dirty, use the cleaning bag to wipe them. If needed, rinse with mild soap and warm water. **Disclaimer: Not suitable for direct observation of the sun. Meets ANSI Z87.1 standards. Z87.1 standard does not apply if Tifosi non-Z87.1 lenses are installed in this frame.**

QR CODE VIDEO LINK
ON REVERSE SIDE



VELOCE / JET FC / LORE

Note: The wider edge of the lens should be closest to the nose bridge when installing.

To Install a Lens:

1. Place the lens anchor into the outside corner of the frame.
2. Pivot the lens back up towards the nose piece making sure that the top of the lens fits into its slot under the top of the frame.
3. Placing the bottom of the lens in your palm and your fingers on top the frame, compress the lens back into its socket until it clicks into place.
4. Repeat steps 1 - 2 with the opposite lens. Lens will be more difficult to install due to Z87.1 rating.
5. Using your Tifosi® Microfiber cleaning bag, wipe any fingerprints off the lenses.



www.tifositactical.com

www.tifosioptics.com

Scan QR Code for how-to video:

